

www.china-supreme.com

为时尚产业 提供智能制造解决方案

*Intelligent manufacturing
Solutions for fashion industries*

SP-600

热风压缝机

HOT AIR SEAM SEALING MACHINE




SUPREME

创新 · 智造
Innovation & Creation

SP-600 热风压缝机



防护服
Medical protective clothing



热风压缝机主要用于缝口密封，是一道压胶补强工艺，在接缝处通过压胶机对胶带进行加热，利用压轮连续旋转送料加压，将胶带紧密粘合在面料的接缝处，防止水、细菌、病毒、空气等通过接缝处侵入内壁，达到防护的作用。广泛适用于医疗防护服、无缝内衣、无缝袜、泳衣、防水鞋、潜水服、登山衣、瑜伽服、防水袋、滑雪衣、雨衣等功能性服装与产品的密封压缝。

Hot-air seam sealing machine is mainly used for seam sealing. It is a glue reinforcement process. The adhesive tape at the seam is heated by the machine, and the pressure roller is continuously rotated to feed and pressurize, and the tape is closely adhered to the fabric, to prevent water, bacteria, viruses, air, etc. from intruding into the inner side through the seam to achieve protection. It is widely used for products such as medical protective clothing, waterproof shoes, diving suits, sports suits, mountaineering suits, waterproof bags, raincoats, tents and awnings etc.

自动送带、自动切带、自动补偿、自动微退，减少损耗提升产能

Fully automatic tape feeding, tape cutting, compensation and micro back, which can reduce waste and increase productivity.

基本参数 Basic parameters

总功率	Total power	5KW	上柱压轮压力	Upper wheel pressure	0.15Mpa
额定电压	Rated voltage	220V	鼓风机功率	Air blower power	370W
额定频率	Rated frequency	50HZ	上轮工作行程	Lifting travel of up wheel	18-30mm
发热管功率	Heating tube power	4KW	压轮宽度	Width of the pinch wheel	25.4mm
最高温度	Maximum temperature	700°C	压轮直径	Diameter of pinch wheel	65mm
总气压	Air pressure	0.35-0.5Mpa	热风枪嘴宽度	Width of air gun nozzle	22mm
毛重	Gross weight	154KG	外包装尺寸	Package size	L1250 x W650 x H1550mm
净重	Net weight	116KG			

以上型号仅供参考，详细情况请咨询当地经销商。
The above types are only for reference, and you can consult local distributors for details.

为了改良，产品规格若有变更，恕不另行通知。为安全起见，使用之前，请仔细阅读使用手册。
Specifications are subject to change for improvement without further notice. Please carefully read the operating manual before use for safety.